


DQC H-SERIES ISO-B POPPET VALVE FEMALE THREADED COUPLER



* Referential image

** Some features may vary without prior notice. Sale subject to inventory availability

DATE

: 07/09/2026 04:23 PM

SKU

: 22928

BRAND

: DIXON VALVE

MODEL

: 8HBF8

Features:

Poppet style shut-off valves

Construction:

Machined components are manufactured using solid bar stock

Stainless steel balls, retaining rings and springs maximize corrosion resistance and extend service life.

Steel componentry is plated using ROHS Compliant Trivalent Chrome.

Steel coupler sleeves are hardened to resist deformation and maximize service life.

Nitrile (Buna-N) seals are standard

Redundant o-ring sealing system with PTFE backup ring

Valve seals are crimped in place to maintain integrity during excessive flow conditions and pressurized connection.

Available Options:

Contact Dixon for all available option adders

Standard seal options include: FKM, EPDM, Steam-EP, FDA FKM, Mil-Nitrile, Fuel Nitrile, PTFE and Silicone

Kalrez® seal options include: 4079, 6375 and 7075

Valve options include: Unvalved, actuator, steel, brass, 303 stainless steel and 316 stainless steel

Sleeve options include: Sleeve-lock, Flanged and Silicone-flanged

Oxy-clean treatment is available

Compatibility & Interchange Data:

Meets dimensional requirements of ISO 7241 Series B

Interchangeable with Parker-Hannifin 60 Series, Snap-Tite 72-Series, Hansen HK-Series, Faster Series 'HNV', Aeroquip/Eaton FD45, Stucchi Series IRB/IRBO/IRBX

Safety notes:

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Body Size	1"
Burst Pressure	16000 PSI (1100 bar)
Factory Part Number	8HBF8
Hex	1-5/8"
Length	4.13" (104.9mm)
Material	Steel
Maximum OD	2.49" (63.2mm)
Maximum Operating Pressure	4000 PSI (275 bar)
Temperature Range	-40°F to +250°F (-40°C to +121°C)
Thread	Female BSPP
Thread Size	1"-11
Weight Lb	1.7800