


DQC HS-SERIES ISO-B STEAM INTERCHANGE FEMALE COUPLER



* Referential image

** Some features may vary without prior notice. Sale subject to inventory availability

DATE

: 07/09/2026 08:18 PM

SKU

: 22944

BRAND

: DIXON VALVE

MODEL

: 8HSF8-S

Applications:

Designed exclusively for steam applications

Construction:

Machined components are manufactured using solid bar stock

Stainless steel balls, retaining rings and springs maximize corrosion resistance and extend service life.

Coupler has a large plated steel sleeve designed for easy gripping with gloves
Steel componentry is plated using ROHS Compliant Trivalent Chrome.

EPDM steam-grade seals are standard

Couplers have a redundant O-Ring sealing system (Dual O-rings with PTFE back-up)

Valve seals are crimped in place to maintain integrity during excessive flow conditions.

Special high-temp EPDM O-rings designed for steam service

Compatibility & Interchange Data:

Interchangeable to ISO7241 Series 'B'

Parker 60-Series Steam Couplings

Safety notes:

Maximum working pressure has been calculated using standard saturated steam at 194°C (382°F) for general purpose continuous service. For advanced operating pressure or super-heated steam applications, contact Dixon for further information.

Warning: Do not disconnect under pressure!

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Body Size	1"
Factory Part Number	8HSF8-S
Hex	1-5/8"
Length	4.13" (104.9mm)
Material	303 Stainless Steel
Maximum OD	2.94" (74.7mm)
Pressure Rating	Rated to 200 PSI gauge saturated steam 382°F (194°C)
Temperature Range	-70°F to +400°F (-57°C to +204°C)
Thread	Female NPTF
Thread Size	1" - 11-1/2
Weight Lb	0.3900