

GRAVITY UTILITY NOZZLE

DATE

: 04/14/2026 09:38 PM

SKU

: 6644

BRAND

: DIXON VALVE

MODEL

: 900S34



Applications:

These delivery nozzles are ideally suited for low pressure use such as agricultural and 12 volt truck utility pumps, or gravity flow fittings in economy applications

Features:

Nozzles are manual operation, they do not have an automatic flow shut off.

Rugged design

Good flow rating

Construction:

Die cast zinc aluminum body

Plated steel trigger

Buna seals

Aluminum spout

Steel reducer bushing

Note:

Nozzles with a 3/4" female NPT inlet, use a 1" x 3/4" steel reducer bushing to achieve 3/4" female NPT inlet (included)

All fuel contains additives, which can vary by fuel brand and season. Please contact Dixon with a list of all additives and we will advise of any known compatibility issues.

Safety notes:

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

* Referential image

** Some features may vary without prior notice. Sale subject to inventory availability

TECHNICAL SPECIFICATIONS

Flow	95 GPM at 20 PSI
Inlet	3/4" female NPT
Material	Die cast zinc aluminum
Maximum Operating Pressure	25 PSI
Outlet	3/4" Straight Spout
Factory Part Number	900S34
Weight Lb	2.0000