

## DOUBLE CLAPPER SIAMESE CONNECTION BOTTOM OUTLET



\* Referential image

\*\* Some features may vary without prior notice. Sale subject to inventory availability

DATE

: 04/21/2026 10:18 PM

SKU

: 6660

BRAND

: DIXON VALVE

MODEL

: 90DCS4025F-SP

### Applications:

Provides the required 500 GPM minimum to supplement the fire protection as an auxiliary inlet connection to the water supply. (250 GPM minimum per inlet.)

### Specifications:

UL listed

Factory Mutual approved

ULC Listed

### Features:

Exposed Fire Department Connections (FDC) provide an economical method of satisfying local fire codes.

### Safety notes:

WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

## TECHNICAL SPECIFICATIONS

|                                   |                            |
|-----------------------------------|----------------------------|
| <b>Branding</b>                   | Standpipe                  |
| <b>Factory Part Number</b>        | 90DCS4025F-SP              |
| <b>Inlet</b>                      | (2) 2-1/2" female NST (NH) |
| <b>Material</b>                   | Cast Brass                 |
| <b>Maximum Operating Pressure</b> | 175 PSI                    |
| <b>Outlet</b>                     | 4" female NPT              |
| <b>Weight Lb</b>                  | 17.8200                    |