

## SINGLE CLAPPER SIAMESE CONNECTION BOTTOM OUTLET

DATE  
: 07/09/2026 08:19 AM

SKU  
: 6679

BRAND  
: DIXON VALVE

MODEL  
: 90ISCS4025F



**Applications:**

Provides the required 500 GPM minimum to supplement the fire protection as an auxiliary inlet connection to the water supply. (250 GPM minimum per inlet.)

**Specifications:**

UL listed  
ULC listed

**Features:**

The swing clapper design provides an unobstructed waterway.

Exposed Fire Department Connections (FDC) provide an economical method of satisfying local fire codes.

**Construction:**

Single swing clapper with (2) pin lug swivel inlets.

**Available Options:**

Other thread options are available. Consult Dixon for pricing and availability.

**Safety notes:**

WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

*\* Referential image*

*\*\* Some features may vary without prior notice. Sale subject to inventory availability*

**TECHNICAL SPECIFICATIONS**

<b>Branding</b>	Auto-Sprinkler
<b>Factory Part Number</b>	90ISCS4025F
<b>Inlet</b>	(2) 2-1/2" female NST (NH)
<b>Material</b>	Cast Brass
<b>Maximum Operating Pressure</b>	250 PSI
<b>Origin</b>	Global
<b>Outlet</b>	4" female NPT
<b>Weight Lb</b>	8.0000