

POLYPROPYLENE CAM & GROOVE TYPE D 90° ELBOW COUPLER X FEMALE NPT



* Referential image

** Some features may vary without prior notice. Sale subject to inventory availability

DATE

: 06/16/2026 05:26 AM

SKU

: 6685

BRAND

: DIXON VALVE

MODEL

: 90PPD200

Construction:

Manufactured from glass-filled polypropylene

EPDM gaskets

304 stainless steel handles and pins

How it works:

To make a connection, simply slide the adapter into the coupler and with normal hand pressure, press the cam levers down.

Uncoupling is as quick and simple as coupling. Just lift the cam arms and remove the adapter.

Safety notes:

Under no circumstances should cam and groove couplings be used for compressed air or steam service!

Pressure rating recommendations are based on the use of mating Dixon fittings at ambient temperature 70°F / 21°C with a standard seal installed.

For use at elevated temperature or other unusual operating conditions, consult Dixon.

Not recommended for use with PTFE gaskets

Polypropylene cam and groove should not be mixed with metal fittings

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Material	Polypropylene
Maximum Operating Pressure	100 PSI
Factory Part Number	90PPD200
Seal	EPDM
Size	2"
Weight Lb	0.7500