

POLYPROPYLENE CAM & GROOVE TYPE F 90° ELBOW ADAPTER X MALE NPT



* Referential image
** Some features may vary without prior notice. Sale subject to inventory availability

DATE
: 06/16/2026 06:02 AM

SKU
: 6686

BRAND
: DIXON VALVE

MODEL
: 90PPF150

Construction:
Manufactured from glass-filled polypropylene

How it works:
To make a connection, simply slide the adapter into the coupler and with normal hand pressure, press the cam levers down.
Uncoupling is as quick and simple as coupling. Just lift the cam arms and remove the adapter.

Safety notes:
Under no circumstances should cam and groove couplings be used for compressed air or steam service!
Pressure rating recommendations are based on the use of mating Dixon fittings at ambient temperature 70°F / 21°C with a standard seal installed.
For use at elevated temperature or other unusual operating conditions, consult Dixon.
Not recommended for use with PTFE gaskets
Polypropylene cam and groove should not be mixed with metal fittings
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Material	Polypropylene
Maximum Operating Pressure	100 PSI
Factory Part Number	90PPF150
Size	1-1/2"
Weight Lb	0.2400