

## SINGLE CLAPPER SIAMESE CONNECTION BOTTOM OUTLET



\* Referential image

\*\* Some features may vary without prior notice. Sale subject to inventory availability

DATE

: 07/09/2026 08:19 AM

SKU

: 6688

BRAND

: DIXON VALVE

MODEL

: 90SCS4025F

Applications:

Provides the required 500 GPM minimum to supplement the fire protection as an auxiliary inlet connection to the water supply. (250 GPM minimum per inlet.)

Specifications:

UL listed

Features:

The swing clapper design provides an unobstructed waterway.

Exposed Fire Department Connections (FDC) provide an economical method of satisfying local fire codes.

Construction:

Single swing clapper with (2) pin lug swivel inlets.

Available Options:

Other thread options are available. Consult Dixon for pricing and availability.

Safety notes:

WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

## TECHNICAL SPECIFICATIONS

<b>Branding</b>	Auto-Sprinkler
<b>Factory Part Number</b>	90SCS4025F
<b>Inlet</b>	(2) 2-1/2" female NST (NH)
<b>Mandatory Pkg/Box Qty</b>	1
<b>Material</b>	Cast Brass
<b>Maximum Operating Pressure</b>	250 PSI
<b>Origin</b>	U.S.
<b>Outlet</b>	4" female NPT
<b>Weight Lb</b>	12.4000