

## ADS OUTALARM® WITH CAPACITANCE PROBE



DATE  
: 07/08/2026 03:33 AM

SKU  
: 22983

BRAND  
: DIXON VALVE

MODEL  
: A100C12A

### Applications:

Specifically designed for liquid terminal operation on batch loading and overfill protection, unloading, tank cars, tank trucks, marine barges, suitable for open and close dome

### Specifications:

Intrinsically safe design per ANSI/UL913 Class I, Div I Groups A, B, C and D Hazardous Areas

Minimum dielectric constant 1.7

Temperature range: capacitance probe: -14°F to 250°F (-26°C to 121°C)

Activation point 1/4" above liquid surface

Compatible with any liquid or dry bulk material with a dielectric constant of 1.7 or greater

Horn intensity 101 dB at 2'

Light output 3 each 3000 mcd high intensity flashing LED's

Pressure rating on standard unit: 50 PSI, consult Dixon® for applications up to 300 PSI

### Features:

Totally self-contained; no wires, tubing or external power

Rugged weather and corrosion resistant construction

No moving parts, tip sensitive phase shift™ digital capacitance sensor for conductive and nonconductive fluid, conductivity sensor with integral splash shield

Requires no calibration or adjustment

Adjustable insertion length through a standard 1/2" NPT fitting

High intensity audible and flashing visual outputs

Optional opto-isolated solid state contact output

Full, hard graduated laser engraved rod

A100 operates up to 2500 hours on a single 9V alkaline battery

Fail safe continuous battery monitor goes to alarm state on low battery

\* Referential image

\*\* Some features may vary without prior notice. Sale subject to inventory availability

**TECHNICAL SPECIFICATIONS**

<b>Factory Part Number</b>	A100C12A
<b>Length</b>	12"
<b>Pressure Rating</b>	50 PSI, consult Dixon® for applications up to 300 PSI
<b>Temperature Range</b>	-40°F to 325°F (-40°C to 162°C)