

## ADS OUTALARM® WITH CAPACITANCE PROBE



\* Referential image

\*\* Some features may vary without prior notice. Sale subject to inventory availability

DATE

: 07/08/2026 01:51 AM

SKU

: 27291

BRAND

: DIXON VALVE

MODEL

: A100C96A

### Applications:

Specifically designed for liquid terminal operation on batch loading and overfill protection, tank cars, tank trucks, marine barges, suitable for open and close dome

### Specifications:

Intrinsically safe design per ANSI/UL913 Class I, Div I Groups A, B, C and D Hazardous Areas

### Features:

Totally self-contained; no wires, tubing or external power

Rugged weather and corrosion resistant construction

No moving parts, tip sensitive phase shift™ digital capacitance sensor for conductive and non-conductive fluid

Requires no calibration or adjustment

Operates up to 2500 hours on a single 9V alkaline battery

Adjustable insertion length through a standard 1/2" NPT fitting

High intensity audible and flashing visual outputs

Full, hard graduated laser engraved rod

Fail safe continuous battery monitor goes to alarm state on low battery

Activation point 1/4" above liquid surface

Battery current drain

## TECHNICAL SPECIFICATIONS

<b>Length</b>	96"
<b>Factory Part Number</b>	A100C96A
<b>Pressure Rating</b>	50 PSI, consult Dixon® for applications up to 300 PSI
<b>Temperature Range</b>	-14°F to 250°F (-26°C to 121°C)
<b>Weight Lb</b>	4.5000