


A-SERIES PNEUMATIC FEMALE THREADED PLUG



* Referential image

** Some features may vary without prior notice. Sale subject to inventory availability

DATE
: 05/21/2026 03:19 PM

SKU
: 6770

BRAND
: DIXON VALVE

MODEL
: A2F2-B

Applications:

A series couplers are intended for use in compressed air service where the convenience of one hand operation and a compact profile is desired.

Specifications:

Rated pressure for connected Brass Coupler & Brass Plug: 500 PSI (35 bar)
Maximum Working and 6,500 PSI (450 bar) Burst

Construction:

Machined components are manufactured using solid bar stock.

Compatibility & Interchange Data:

Proprietary Astronautics

Safety notes:

Pressure rating given at ambient temperature 70°F (21°C).

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Body Size	1/4"
Factory Part Number	A2F2-B
Flow	25 CFM at 100 PSI
Hex	11/16"
Length	1.56"
Material	Brass
Maximum OD	0.79"
Pressure Rating	See Product Details

TECHNICAL SPECIFICATIONS

Thread	NPTF
Thread Size	1/4"
Weight Lb	0.0700