

**BOSS-LOCK CAM & GROOVE
TYPE D COUPLER X FEMALE
NPT**



* Referential image

** Some features may vary without prior notice. Sale subject to inventory availability

DATE

: 05/21/2026 05:40 PM

SKU

: 23061

BRAND

: DIXON VALVE

MODEL

: AD800

Applications:

Designed for use with liquids, consult Dixon for specific recommendations

Specifications:

No standard exists for the 8" fittings, and generally does not interchange with other manufacturers.

Construction:

Buna-N gasket

Boss-Lock cam arms

Supplied with pull-ring safety clips

Investment stainless steel cam arms

Available Options:

Other gasket types are available, contact Dixon.

How it works:

To make a connection, simply slide the adapter into the coupler and with normal hand pressure, press the cam levers down.

Uncoupling is as quick and simple as coupling. Just lift the cam arms and remove the adapter.

The cast-in lugs allow safety clips to be attached once the lugs are passed through slots in the special cam lever arms providing a positive locking action.

The pull ring safety clip simplifies the locking action on Boss-Lock couplers. No more inserting clips or dangling lanyards, just a twist and it's locked, giving you a low profile positive locking action.

Safety notes:

Under no circumstances should cam and groove couplings be used for compressed air or steam service!

Pressure rating recommendations are based on the use of mating Dixon

fittings at ambient temperature 70°F (21°C) with a standard seal installed. For use at elevated temperature or other unusual operating conditions, consult Dixon.

Dixon and Boss-Lock cam and groove couplings do not interchange in the 8" size.

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Factory Part Number	AD800
Material	356T6 Aluminum
Maximum Operating Pressure	50 PSI
Seal	Buna-N
Size	8"
Weight Lb	6.8500