

BOSS-LOCK CAM & GROOVE COUPLER X FEMALE NPSM



DATE
: 07/08/2026 12:56 AM

SKU
: 23063

BRAND
: DIXON VALVE

MODEL
: ADS400

Applications
Designed for the delivery of dry goods

Specifications
Produced to interchange with all product produced to Commercial Item
Description A-A-59326D

Features
All Boss-Lock™ couplers are supplied with pull-safety clips.

Construction
Buna-N gasket

Available Options
Other gasket types are available, contact Dixon.

How it works
To make a connection, simply slide the adapter into the coupler and with normal hand pressure, press the cam levers down.
Uncoupling is as quick and simple as coupling. Just lift the cam arms and remove the adapter.
The cast-in lugs allow safety clips to be attached once the lugs are passed through slots in the special cam lever arms providing a positive locking action.
The pull ring safety clip simplifies the locking action on Boss-Lock couplers. No more inserting clips or dangling lanyards, just a twist and it's locked, giving you a low profile positive locking action.

Safety notes
Under no circumstances should cam and groove couplings be used for compressed air or steam service!
Pressure rating recommendations are based on the use of mating Dixon

* Referential image
** Some features may vary without prior notice. Sale subject to inventory availability

fittings at ambient temperature 70°F (21°C) with a standard seal installed. For use at elevated temperature or other unusual operating conditions, consult Dixon.

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Material	356T6 Aluminum
Maximum Operating Pressure	100 PSI
Factory Part Number	ADS400
Seal	Buna-N
Size	4"
Weight Lb	2.0400