

**AG-SERIES AGRICULTURAL
BALL VALVE FEMALE
THREADED PLUG**



* Referential image

** Some features may vary without prior notice. Sale subject to inventory availability

DATE
: 07/08/2026 12:26 PM

SKU
: 6944

BRAND
: DIXON VALVE

MODEL
: AG2F2

Construction:
Machined components are manufactured using solid bar stock
Stainless steel balls, retaining rings and springs maximize corrosion resistance and extend service life.
Steel componentry is plated using ROHS Compliant Trivalent Chrome.
Steel nipples are hardened to provide heavy duty performance and resist brinelling.

Compatibility & Interchange Data:
Pioneer Agricultural Interchange
Parker/Pioneer 4000 Series, Faster NS/NV Series
Safeway Series-S20, Stucchi IR-Series

Safety notes:
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Body Size	1/4"
Burst Pressure	24400 PSI (1700 Bar)
Factory Part Number	AG2F2
Hex	3/4"
Length	1.42" (36.0mm)
Material	Steel
Maximum OD	0.84" (21.3mm)
Maximum Operating Pressure	4000 PSI (275 Bar)
Temperature Range	-40°F to +250°F (-40°C to +121°C)

TECHNICAL SPECIFICATIONS

Thread	Female NPTF
Thread Size	1/4"-18
Weight Lb	0.0900