

**AG-SERIES AGRICULTURAL
POPPET VALVE FEMALE
THREADED PLUG**



* Referential image
** Some features may vary without prior notice. Sale subject to inventory availability

DATE
: 05/22/2026 03:15 AM

SKU
: 6950

BRAND
: DIXON VALVE

MODEL
: AG3F3-PV

Construction:

Machined components are manufactured using solid bar stock
Stainless steel balls, retaining rings and springs maximize corrosion resistance and extend service life.

Steel componentry is plated using ROHS Compliant Trivalent Chrome.
Steel nipples are hardened to provide heavy duty performance and resist brinelling.

Compatibility & Interchange Data:

Pioneer Agricultural Interchange
Parker/Pioneer 4000 Series, Faster NS/NV Series
Safeway Series-S20, Stucchi IR-Series

Safety notes:

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Body Size	3/8"
Burst Pressure	23100 PSI (1600 Bar)
Factory Part Number	AG3F3-PV
Hex	15/16"
Length	1.61" (40.9mm)
Material	Steel
Maximum OD	1.05" (26.7mm)
Maximum Operating Pressure	4000 PSI (275 Bar)
Thread	Female NPTF

TECHNICAL SPECIFICATIONS

Thread Size 3/8"-18

Weight Lb 0.1600