

**AG-SERIES AGRICULTURAL
BALL VALVE FEMALE
THREADED PLUG**



* Referential image
** Some features may vary without prior notice. Sale subject to inventory availability

DATE
: 07/08/2026 12:27 PM

SKU
: 6964

BRAND
: DIXON VALVE

MODEL
: AG6F6

Construction:
Machined components are manufactured using solid bar stock
Stainless steel balls, retaining rings and springs maximize corrosion resistance and extend service life.
Steel componentry is plated using ROHS Compliant Trivalent Chrome.

Compatibility & Interchange Data:
Pioneer Agricultural Interchange
Parker/Pioneer 4000 Series, Faster NS/NV Series
Safeway Series-S20, Stucchi IR-Series

Safety notes:
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

| | |
|-----------------------------------|-----------------------------------|
| Body Size | 3/4" |
| Burst Pressure | 15800 PSI (1050 Bar) |
| Factory Part Number | AG6F6 |
| Hex | 1-3/8" |
| Length | 2.30" (58.4mm) |
| Material | Steel |
| Maximum OD | 1.51" (38.4mm) |
| Maximum Operating Pressure | 3000 PSI (200 Bar) |
| Temperature Range | -40°F to +250°F (-40°C to +121°C) |
| Thread | Female NPTF |



Weight Lb

0.4400