

**VENT-LOCK? SAFETY EZ  
BOSS-LOCK? CAM & GROOVE  
TYPE C COUPLER X HOSE  
SHANK**



\* Referential image

\*\* Some features may vary without prior notice. Sale subject to inventory availability

DATE

: 06/16/2026 09:58 AM

SKU

: 7037

BRAND

: DIXON VALVE

MODEL

: ALC400EZ

Applications:

Transfer of fluids and solids, with a safe disconnection

Use:

Can be used with ferrules, sleeves, bands and other reliable attachment options

Features:

Safety release cam and groove couplings permit the release of static pressure when disconnecting hose assemblies

Venting system protects the operator from being sprayed with hazardous or non-hazardous fluids or solids

Safety orange cam arms

Drop shank

US Pat. 934759, CDN Pat. 277866

Construction:

Drop shank

Available Options:

Consult Dixon for availability of other materials

Safety notes:

Pressure rating recommendation is based on the use of mating Vent-Lock™ L-style fittings at ambient temperature 70°F (21°C) with standard Buna-N seal installed, for use at elevated temperature or other unusual operating conditions, consult Dixon.

Does not interchange with standard cam and groove products use only with Vent-Lock™ L-style fittings.

WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

## TECHNICAL SPECIFICATIONS

<b>Material</b>	Aluminum
<b>Maximum Operating Pressure</b>	150 PSI (with King Crimp? Ferrules), 125 PSI (with Crimp Sleeves and Bands)
<b>Factory Part Number</b>	ALC400EZ
<b>Seal</b>	Buna-N
<b>Size</b>	4"
<b>Weight Lb</b>	2.8530