

## ANSI SPLIT FLANGE- SERIES SF

DATE

: 04/20/2026 09:55 AM

SKU

: 23073

BRAND

: DIXON VALVE

MODEL

: ANSI20

Applications:

Provides a direct connection between a grooved adapter and an ANSI Class 125 and 150 raised face flanged component.

Use:

Can be used with flat face flanges by removing the raised projections on the outside face of the flange

Specifications:

Underwriters Listed

Factory Mutual approved

Bolts: 4

Bolt Size: 5/8"

Bolt Length: 5/8"

Features:

Comparable to Victaulic's #741 and Grinnell's #7012

Construction:

Rust inhibiting paint


EPDM gasket

Available Options:

Buna gaskets are available upon request, contact Dixon.

Safety notes:

WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)



\* Referential image

\*\* Some features may vary without prior notice. Sale subject to inventory availability

**TECHNICAL SPECIFICATIONS**

<b>Factory Part Number</b>	ANSI20
<b>Material</b>	Ductile Iron
<b>Maximum Operating Pressure</b>	300 PSI at 70°F(21°C)
<b>Nominal Size</b>	2"
<b>Pipe OD</b>	2.375"
<b>Weight Lb</b>	3.6000