

## ANSI SPLIT FLANGE- SERIES SF

DATE  
: 04/20/2026 09:56 AM

SKU  
: 23075

BRAND  
: DIXON VALVE

MODEL  
: ANSI30

**Applications:**

Provides a direct connection between a grooved adapter and an ANSI Class 125 and 150 raised face flanged component.

**Use:**

Can be used with flat face flanges by removing the raised projections on the outside face of the flange

**Specifications:**

Underwriters Listed  
Factory Mutual approved  
Bolts: 4  
Bolt Size: 5/8"  
Bolt Length: 5/8"

**Features:**

Comparable to Victaulic's #741 and Grinnell's #7012

**Construction:**

Rust inhibiting paint  
EPDM gasket

**Available Options:**

Buna gaskets are available upon request, contact Dixon.

**Safety notes:**

WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)



\* Referential image

\*\* Some features may vary without prior notice. Sale subject to inventory availability

**TECHNICAL SPECIFICATIONS**

<b>Factory Part Number</b>	ANSI30
<b>Material</b>	Ductile Iron
<b>Maximum Operating Pressure</b>	300 PSI at 70°F(21°C)
<b>Nominal Size</b>	3"
<b>Pipe OD</b>	3.50"
<b>Weight Lb</b>	4.9000