

## SAND BLAST QUICK COUPLING



\* Referential image

\*\* Some features may vary without prior notice. Sale subject to inventory availability

DATE  
: 07/08/2026 12:43 AM

SKU  
: 7116

BRAND  
: DIXON VALVE

MODEL  
: ASB125

### Applications:

Sand blast couplings are designed for use on sand blast hose.

### Features:

Supplied with screws

### Installation

Ends of hose must be cut square to fit snug against metal end.

Holding hose tight to end of fitting, insert screws and turn in full, putting screw 180° from first to ensure best centering.

After all screws have been placed, check tube opposite screws to be sure screws have not penetrated completely through.

On quick couplings, insert safety clips.

### Safety notes:

Abrasive blasting equipment must have hose safety cables or hose coupling safety clips installed

WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

## TECHNICAL SPECIFICATIONS

<b>Factory Part Number</b>	ASB125
<b>Hose OD</b>	2-5/32"
<b>Hose Size</b>	1-1/4"
<b>Material</b>	Aluminum
<b>Pressure Rating</b>	110 PSI at ambient temperature 70°F (21°C)
<b>Weight Lb</b>	0.7500

**TECHNICAL SPECIFICATIONS**