

THERMAL-GARD? ELEVATED TEMPERATURE SPRAY NOZZLE



* Referential image

** Some features may vary without prior notice. Sale subject to inventory availability

DATE
: 04/17/2026 11:04 AM

SKU
: 7223

BRAND
: DIXON VALVE

MODEL
: AWSG-TG

Features:

Nozzle protects the operator from extreme hot water temperatures that exceed the comfort zone of standard hot water nozzles.

Thermal insulating sleeve reduces overall heat during elevated temperature conditions.

Construction:

Lightweight aluminum alloy body reduces overall weight.

Aluminum alloy body is electroless nickel plated for additional corrosion protection.

Stainless steel lever handle is coated for additional thermal protection, and operator comfort.

Black cover

3/8" female NPT inlet

Required special rigid, stainless steel adapter, (3/8" male NPT x 1/2" female NPT) included

Safety notes:

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Factory Part Number	AWSG-TG
Flow	12.5 GPM
Material	Aluminum
Temperature Range	140°F to 200°F (60°C to 93°C) Water
Weight Lb	2.1700
Working Pressure	150 PSI

TECHNICAL SPECIFICATIONS