

## WILKERSON FRL'S B18 COMPACT FILTER/REGULATOR



DATE  
: 07/08/2026 11:04 PM

SKU  
: 26056

BRAND  
: DIXON VALVE

MODEL  
: B18-03AG

### Applications:

Over-under units are space savers and provide for installation in tight areas. One common inlet/outlet for both filter and regulator saves on piping costs.

### Use:

To increase regulated pressure, pull adjusting knob and turn clockwise. To reduce pressure, turn knob counter clockwise. To lock knob, push down.

Two 1/4" gauge ports located on the front and rear faces of the body. These ports may be used as additional regulated ports or for pressure gauges. Plug unused port(s).

### Features:

- 5- 125 PSIG adjusting range for transparent bowl with guard
- 5 micron element
- 1.72 oz. bowl
- Self-relieving standard
- Spring-loaded diaphragm
- Transparent Bowl supplied with GC230 gauge

### Safety notes:

Designed for air service only!

SCFM ratings at 100 PSIG inlet pressure

WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

\* Referential image

\*\* Some features may vary without prior notice. Sale subject to inventory availability

**TECHNICAL SPECIFICATIONS**

<b>Description</b>	Automatic Drain, Transparent Bowl and Guard
<b>Factory Part Number</b>	B18-03AG
<b>Flow</b>	158 SCFM
<b>Mandatory Pkg/Box Qty</b>	1
<b>Maximum Operating Pressure</b>	150 PSIG (10.3 Bar)
<b>Port</b>	3/8"
<b>Temperature Range</b>	32°F to 125°F (0°C to 52°C)
<b>Weight Lb</b>	1.6800