

WILKERSON FRL'S B18 COMPACT FILTER/REGULATOR



DATE
: 07/08/2026 11:19 PM

SKU
: 26058

BRAND
: DIXON VALVE

MODEL
: B18-03MG

Applications:

Over-under units are space savers and provide for installation in tight areas. One common inlet/outlet for both filter and regulator saves on piping costs.

Use:

To increase regulated pressure, pull adjusting knob and turn clockwise. To reduce pressure, turn knob counter clockwise. To lock knob, push down.

Two 1/4" gauge ports located on the front and rear faces of the body. These ports may be used as additional regulated ports or for pressure gauges. Plug unused port(s).

Features:

- 5- 125 PSIG adjusting range for transparent bowl with guard
- 5 micron element
- 1.72 oz. bowl
- Self-relieving standard
- Spring-loaded diaphragm
- Transparent Bowl supplied with GC230 gauge

Safety notes:

Designed for air service only!

SCFM ratings at 100 PSIG inlet pressure

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

* Referential image

** Some features may vary without prior notice. Sale subject to inventory availability

TECHNICAL SPECIFICATIONS

Description	Manual Drain, Transparent Bowl and Guard
Factory Part Number	B18-03MG
Flow	158 SCFM
Mandatory Pkg/Box Qty	1
Maximum Operating Pressure	150 PSIG (10.3 Bar)
Port	3/8"
Temperature Range	32°F to 125°F (0°C to 52°C)
Weight Lb	1.6600