

## WILKERSON FRL'S B18 COMPACT FILTER/REGULATOR



DATE  
: 04/23/2026 06:38 AM

SKU  
: 26063

BRAND  
: DIXON VALVE

MODEL  
: B18-04MGMB

### Applications:

Over-under units are space savers and provide for installation in tight areas. One common inlet/outlet for both filter and regulator saves on piping costs.

### Use:

To increase regulated pressure, pull adjusting knob and turn clockwise. To reduce pressure, turn knob counter clockwise. To lock knob, push down.

Two 1/4" gauge ports located on the front and rear faces of the body. These ports may be used as additional regulated ports or for pressure gauges. Plug unused port(s).

### Features:

- 10-250 PSIG adjusting range for metal bowl with sight glass
- 5 micron element
- 1.72 oz. bowl
- Self-relieving standard
- Spring-loaded diaphragm
- Metal bowl supplied with GC240 gauge

### Safety notes:

FRL's are designed for air service only, unless otherwise indicated.

SCFM ratings at 100 PSIG inlet pressure

WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

\* Referential image

\*\* Some features may vary without prior notice. Sale subject to inventory availability

## TECHNICAL SPECIFICATIONS

|                                   |   |
|-----------------------------------|---|
| <b>Description</b>                | Manual Drain, Metal Bowl with Sight Glass |
| <b>Factory Part Number</b>        | B18-04MGMB                                |
| <b>Flow</b>                       | 121 SCFM                                  |
| <b>Mandatory Pkg/Box Qty</b>      | 1   |
| <b>Maximum Operating Pressure</b> | 250 PSIG (17.2 Bar)                       |
| <b>Port</b>                       | 1/2"                                      |
| <b>Temperature Range</b>          | 32°F to 150°F (0°C to 65.5°C)             |
| <b>Weight Lb</b>                  | 2.3400                                    |