

WILKERSON FRL'S B28 STANDARD FILTER/REGULATOR



* Referential image

** Some features may vary without prior notice. Sale subject to inventory availability

DATE

: 04/23/2026 07:57 AM

SKU

: 26067

BRAND

: DIXON VALVE

MODEL

: B28-03MGMB

Applications:

Over-under units are space savers and provide for installation in tight areas. One common inlet/outlet for both filter and regulator saves on piping costs.

Use:

To increase regulated pressure, pull adjusting knob and turn clockwise. To reduce pressure, turn knob counter clockwise. To lock knob, push down.

Features:

10-250 PSIG adjusting range for metal bowl with sight glass

5 micron element

2.87 oz. bowl

Self-relieving standard

Spring-loaded diaphragm

Two 1/4" gauge ports located on the front and rear faces of the body. These ports may be used as additional regulated ports or for pressure gauges. Plug unused port(s).

Metal bowl supplied with GC240 gauge

Safety notes:

FRL's are designed for air service only, unless otherwise indicated.

SCFM ratings at 100 PSIG inlet pressure

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Description	Manual Drain, Metal Bowl with Sight Glass
Factory Part Number	B28-03MGMB
Flow	200 SCFM
Mandatory Pkg/Box Qty	1
Maximum Operating Pressure	250 PSIG (17.2 Bar)
Port	3/8"
Temperature Range	32°F to 150°F (0°C to 65.5°C)
Weight Lb	4.4900