

WILKERSON FRL'S B28 STANDARD FILTER/REGULATOR



* Referential image

** Some features may vary without prior notice. Sale subject to inventory availability



DATE

: 04/23/2026 07:56 AM

SKU

: 26072

BRAND

: DIXON VALVE

MODEL

: B28-06AG

Applications:

Over-under units are space savers and provide for installation in tight areas. One common inlet/outlet for both filter and regulator saves on piping costs.

Use:

To increase regulated pressure, pull adjusting knob and turn clockwise. To reduce pressure, turn knob counter clockwise. To lock knob, push down.

Features:

5-125 PSIG adjusting range for transparent bowl with guard

5 micron element

2.87 oz. bowl

Self-relieving standard

Spring-loaded diaphragm

Two 1/4" gauge ports located on the front and rear faces of the body. These ports may be used as additional regulated ports or for pressure gauges. Plug unused port(s).

Transparent bowl supplied with GC230 gauge

Safety notes:

FRL's are designed for air service only, unless otherwise indicated.

SCFM ratings at 100 PSIG inlet pressure

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Description	Automatic Drain, Transparent Bowl and Guard
Factory Part Number	B28-06AG
Flow	235 SCFM
Mandatory Pkg/Box Qty	1
Maximum Operating Pressure	150 PSIG (10.3 Bar)
Port	3/4"
Temperature Range	32°F to 125°F (0°C to 52°C)
Weight Lb	2.2800