

## WILKERSON FRL'S B28 STANDARD FILTER/REGULATOR



DATE  
: 04/23/2026 07:56 AM

SKU  
: 26073

BRAND  
: DIXON VALVE

MODEL  
: B28-06AGMB

### Applications:

Over-under units are space savers and provide for installation in tight areas. One common inlet/outlet for both filter and regulator saves on piping costs.

### Use:

To increase regulated pressure, pull adjusting knob and turn clockwise. To reduce pressure, turn knob counter clockwise. To lock knob, push down.

### Features:

10-250 PSIG adjusting range for metal bowl with sight glass

5 micron element

2.87 oz. bowl

Self-relieving standard

Spring-loaded diaphragm

Two 1/4" gauge ports located on the front and rear faces of the body. These ports may be used as additional regulated ports or for pressure gauges. Plug unused port(s).

Metal bowl supplied with GC240 gauge

### Safety notes:

FRL's are designed for air service only, unless otherwise indicated.

SCFM ratings at 100 PSIG inlet pressure

WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

\* Referential image

\*\* Some features may vary without prior notice. Sale subject to inventory availability

### TECHNICAL SPECIFICATIONS

<b>Description</b>	Automatic Drain, Metal Bowl with Sight Glass
<b>Factory Part Number</b>	B28-06AGMB
<b>Flow</b>	235 SCFM
<b>Mandatory Pkg/Box Qty</b>	1
<b>Maximum Operating Pressure</b>	250 PSIG (17.2 Bar)
<b>Port</b>	3/4"
<b>Temperature Range</b>	32°F to 150°F (0°C to 65.5°C)
<b>Weight Lb</b>	2.7500