

## AIR BLOW CHECK VALVE QUICK-CONNECT PLUG



\* Referential image

\*\* Some features may vary without prior notice. Sale subject to inventory availability

**KMX**  
INDUSTRIAL EQUIPMENT

DATE

: 07/08/2026 06:26 AM

SKU

: 8119

BRAND

: DIXON VALVE

MODEL

: B45AB-R250

Applications:

The air blow check valve is designed to pressurize lines with air to clean out product or cleaning solutions. It is fail-safe because the simple air-to-open, spring-to-close mechanism prevents backflow. Can be used with a check valve.

Specifications:

3A authorized 58-00

Construction:

EPDM stem seat and gasket

Note:

Filter disc (optional) must be used when installed for Accepted Practice 3A 604-05, Supplying Air under Pressure in Contact with Milk, Milk products and Product Contact.

Safety notes:

WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

### TECHNICAL SPECIFICATIONS

<b>Factory Part Number</b>	B45AB-R250
<b>Material</b>	316L Stainless Steel
<b>Maximum Operating Pressure</b>	145 PSI
<b>Maximum Temperature</b>	212°F (100°C)
<b>Seat</b>	EPDM stem seat and gasket
<b>Size</b>	2-1/2"

**TECHNICAL SPECIFICATIONS**

**Weight Lb**

1.5400