

## B5102 SERIES BUTTERFLY VALVE

DATE

: 04/21/2026 02:47 AM

SKU

: 8374

BRAND

: DIXON VALVE

MODEL

: B5102E100-A

Specifications:

Break torque: 125 in. lbs.

Assembly torque: 36 in. lbs.

Flow coefficient: 23 CV

Features:

All sizes use only 3/4" of line space

The grooved clamp housing connects directly to the corresponding sanitary clamp size

100% tested / 100% inspected

Field serviceable (no special tools required)

Construction:

All wetted surfaces are sanitary finish 316L stainless steel

PTFE valve disc bushings reduce friction and increase cycle life

3-position reversible handle

Available Options:

Various automatic operations available

Can be modified for lockout / tagout

Note:

Pressure rating (PSI), Flow Coefficient (CV), Assembly Torque (in. lbs.) and Break Torque (in. lbs.) information supplied is based on water media at 68°F

Safety notes:

WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)



\* Referential image

\*\* Some features may vary without prior notice. Sale subject to inventory availability

**TECHNICAL SPECIFICATIONS**

<b>Factory Part Number</b>	B5102E100-A
<b>Material</b>	316L Stainless Steel
<b>Pressure Rating</b>	140 PSI,  0.4 inches Hg vacuum @ 68°F minimal line
<b>Seat</b>	EPDM
<b>Size</b>	1"
<b>Temperature Range</b>	15°F to 200°F (-9.4°C to 93°C)
<b>Weight Lb</b>	2.4050