

BAYONET STYLE DRY DISCONNECT ADAPTER X FEMALE NPT



* Referential image

** Some features may vary without prior notice. Sale subject to inventory availability

DATE

: 07/08/2026 06:25 AM

SKU

: 8703

BRAND

: DIXON VALVE

MODEL

: BA62-300

Applications:

Bayonet dry disconnect fittings are ideally suited for the spill-less transfer of petroleum products such as fuel oil, lube oil blending, and tank truck delivery. The design of the Bayco bayonet dry disconnect system ensures a spill free connection, fluid cannot flow until couplings are connected together and the valve is opened. The coupling can then not be disconnected until the valve handle is closed.

Specifications:

Canadian registration number CRN# OH14055 all provinces

Features:

Helps eliminate the possibility of costly spills

Construction:

Anodized aluminum poppet valve

Compatibility & Interchange Data:

Interchangeable with the Emco Wheaton™ Dry Break™

Note:

Rubber dust caps with stainless steel chains are available to protect the adapter from contamination and damage.

Safety notes:

For pressure ratings at other temperatures contact Dixon®.

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Factory Part Number	BA62-300
Material	Aluminum
Maximum Operating Pressure	85 PSI at 70°F (21°C)
Seal	FKM
Size	3"
Weight Lb	2.5800