

## BACKFLOW PREVENTER

DATE  
: 07/08/2026 01:51 AM

SKU  
: 8908

BRAND  
: DIXON VALVE

MODEL  
: BFP200



### Applications:

Designed to give maximum protection against backflow caused by back-pressure or back-siphonage from a cross-connection wherein a contaminant hazard exists (i.e. a health hazard), or a pollutant hazard exists (i.e. a non-hazard).

### Specifications:

Underwriters listed

Factory Mutual approved

Meets Foundation for Cross Connection Control and Hydraulic Research at University of Southern California Manual Section 10, ASSE 1015, AWWA C-510 and CSA B64.4 specifications

### Features:

Consists of two spring-loaded poppet type valves and a mechanically independent, hydraulically dependent pressure differential relief valve

Three top mounted test cocks ensure easy access during repair and maintenance when unit is installed in tight places

### Note:

Create a Fire Hydrant Backflow Preventer using the RSMSA25F20T and the DMH2025F

### Safety notes:

WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

\* Referential image

\*\* Some features may vary without prior notice. Sale subject to inventory availability

## TECHNICAL SPECIFICATIONS

<b>Material</b>	Brass
<b>Factory Part Number</b>	BFP200
<b>Temperature Range</b>	33°F to 180°F (.6°C to 82°C)
<b>Thread</b>	NPT
<b>Thread Size</b>	2"
<b>Weight Lb</b>	40.1000
<b>Working Pressure</b>	175 PSIG