

BR-SERIES PNEUMATIC MALE THREADED PLUG



* Referential image

** Some features may vary without prior notice. Sale subject to inventory availability

DATE
: 05/22/2026 06:58 AM

SKU
: 9134

BRAND
: DIXON VALVE

MODEL
: BR1M1-B-E-7

Construction:

Machined components are manufactured using solid brass bar stock.
Machined components are plated with chrome-over-nickel plating.

Compatibility & Interchange Data:

Rectus 21KA, Tomco Series SC, CEJN Series 223

Safety notes:

It is important to be safe when installing quick disconnect couplings into a pneumatic circuit. Never install a pneumatic coupling directly into an air tool, use a piece of hose that is at least 18" long, between the tool and the coupling, to prevent damage to the coupling. To protect the operator, safety devices, such as a safety check valve and safety cable should be installed in case there is a hose or coupling failure.

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

| | |
|-----------------------------------|-----------------------------------|
| Body Size | 1/8" |
| Burst Pressure | 7000 PSI |
| Factory Part Number | BR1M1-B-E-7 |
| Hex | 9/16" |
| Length | 1.06" |
| Material | Brass |
| Maximum OD | 0.65" |
| Maximum Operating Pressure | 300 PSI |
| Temperature Range | -40°F to +250°F (-40°C to +121°C) |

TECHNICAL SPECIFICATIONS

| | |
|--------------------|--------|
| Thread | NPT |
| Thread Size | 1/8" |
| Weight Lb | 0.0280 |