

## BR-SERIES PNEUMATIC MALE THREADED PLUG



\* Referential image

\*\* Some features may vary without prior notice. Sale subject to inventory availability

DATE

: 05/22/2026 06:48 AM

SKU

: 9135

BRAND

: DIXON VALVE

MODEL

: BR1M2-B-E-7

Construction:

Machined components are manufactured using solid brass bar stock.

Machined components are plated with chrome-over-nickel plating.

Compatibility & Interchange Data:

Rectus 21KA, Tomco Series SC, CEJN Series 223

Safety notes:

It is important to be safe when installing quick disconnect couplings into a pneumatic circuit. Never install a pneumatic coupling directly into an air tool, use a piece of hose that is at least 18" long, between the tool and the coupling, to prevent damage to the coupling. To protect the operator, safety devices, such as a safety check valve and safety cable should be installed in case there is a hose or coupling failure.

WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

### TECHNICAL SPECIFICATIONS

<b>Body Size</b>	1/8"
<b>Burst Pressure</b>	7000 PSI
<b>Factory Part Number</b>	BR1M2-B-E-7
<b>Hex</b>	5/8"
<b>Length</b>	1.20"
<b>Material</b>	Brass
<b>Maximum OD</b>	0.72"
<b>Maximum Operating Pressure</b>	300 PSI
<b>Temperature Range</b>	-40°F to +250°F (-40°C to +121°C)

**TECHNICAL SPECIFICATIONS**

<b>Thread</b>	NPT
<b>Thread Size</b>	1/4"
<b>Weight Lb</b>	0.0400