

**GROOVED STANDARD  
COUPLING- SERIES S, STYLE 11**



\* Referential image

\*\* Some features may vary without prior notice. Sale subject to inventory availability

DATE

: 04/22/2026 04:27 PM

SKU

: 23366

BRAND

: DIXON VALVE

MODEL

: C12BU

Applications:

Designed for a wide range of applications including commercial/industrial construction, mining, and process piping.

Specifications:

Underwriters Listed

Factory Mutual approved

Bolts: 2

Bolt Size: 1/2"

Bolt Length: 2-3/4"

Features:

Housing design allows for optimum strength without excessive casting weight

Comparable to Victaulic's #77 and Grinnell's #7001

Construction:

Rust inhibiting paint

Safety notes:

WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

**TECHNICAL SPECIFICATIONS**

<b>Factory Part Number</b>	C12BU
<b>Material</b>	Ductile Iron
<b>Max. End Load Lbs.</b>	4430
<b>Maximum Operating Pressure</b>	1000 PSI at 70°F (21°C)
<b>Nominal Size</b>	2"
<b>Pipe OD</b>	2.375"
<b>Seal</b>	Buna-N
<b>Weight Lb</b>	2.8000