

## GROOVED STANDARD COUPLING- SERIES S, STYLE 11



\* Referential image

\*\* Some features may vary without prior notice. Sale subject to inventory availability

DATE

: 07/08/2026 02:59 PM

SKU

: 23368

BRAND

: DIXON VALVE

MODEL

: C13

Applications:

Designed for a wide range of applications including commercial/industrial construction, mining, and process piping.

Specifications:

Underwriters Listed

Factory Mutual approved

Bolts: 2

Bolt Size: 1/2"

Bolt Length: 3"

Features:

Housing design allows for optimum strength without excessive casting weight

Comparable to Victaulic's #77 and Grinnell's #7001

Construction:

Rust inhibiting paint

Safety notes:

WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

**TECHNICAL SPECIFICATIONS**

|                                   |                         |
|-----------------------------------|-------------------------|
| <b>Factory Part Number</b>        | C13                     |
| <b>Material</b>                   | Ductile Iron            |
| <b>Max. End Load Lbs.</b>         | 9621                    |
| <b>Maximum Operating Pressure</b> | 1000 PSI at 70°F (21°C) |
| <b>Nominal Size</b>               | 3"                      |
| <b>Pipe OD</b>                    | 3.50"                   |
| <b>Seal</b>                       | EPDM                    |
| <b>Weight Lb</b>                  | 3.9900                  |