

**WILKERSON FRL'S C16
COMPACT COMBINATION UNIT**



* Referential image

** Some features may vary without prior notice. Sale subject to inventory availability

DATE
: 07/09/2026 12:01 AM

SKU
: 26132

BRAND
: DIXON VALVE

MODEL
: C16-02A

Features:

- Automatic Drain
- Transparent Bowl and Guard
- F16 series Filter has a 5 micron element and 5 oz. bowl
- R16 series Regulator is self relieving, has a 0-125 PSI adjusting range and is supplied with a GC230 gauge
- L16 series Lubricator has a 5 oz. bowl, an adjustable oil feed and a full view sight dome
- (2) modular sleeves, (2) mounting brackets (sleeve and bracket) and (2) end blocks are included

Safety notes:

- FRL's are designed for air service only, unless otherwise indicated.
- SCFM ratings at 150 PSIG inlet pressure
- WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Description	Automatic Drain, Transparent Bowl and Guard
Factory Part Number	C16-02A
Flow	36.1 SCFM
Mandatory Pkg/Box Qty	1
Maximum Operating Pressure	150 PSIG (10.3 Bar)
Port	1/4"
Temperature Range	32°F to 125°F (0°C to 52°C)
Weight Lb	6.9000

TECHNICAL SPECIFICATIONS