

WILKERSON FRL'S C16 COMPACT COMBINATION UNIT



* Referential image

** Some features may vary without prior notice. Sale subject to inventory availability

DATE

: 04/23/2026 09:34 AM

SKU

: 26137

BRAND

: DIXON VALVE

MODEL

: C16-03M

Features:

Manual Drain

Transparent Bowl and Guard

F16 series Filter has a 5 micron element and 5 oz. bowl

R16 series Regulator is self relieving, has a 0-125 PSI adjusting range and is supplied with a GC230 gauge

L16 series Lubricator has a 5 oz. bowl, an adjustable oil feed and a full view sight dome

(2) modular sleeves, (2) mounting brackets (sleeve and bracket) and (2) end blocks are included

Safety notes:

FRL's are designed for air service only, unless otherwise indicated.

SCFM ratings at 150 PSIG inlet pressure

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Description	Manual Drain, Transparent Bowl and Guard
Factory Part Number	C16-03M
Flow	58.5 SCFM
Mandatory Pkg/Box Qty	1
Maximum Operating Pressure	150 PSIG (10.3 Bar)
Port	3/8"
Temperature Range	32°F to 125°F (0°C to 52°C)
Weight Lb	6.7080

TECHNICAL SPECIFICATIONS