

## GROOVED STANDARD COUPLING- SERIES S, STYLE 11



DATE  
: 07/08/2026 02:02 PM

SKU  
: 23375

BRAND  
: DIXON VALVE

MODEL  
: C16BU

### Applications:

Designed for a wide range of applications including commercial/industrial construction, mining, and process piping.

### Specifications:

Underwriters Listed  
Factory Mutual approved  
Bolts: 2  
Bolt Size: 3/4"  
Bolt Length: 4-1/4"

### Features:

Housing design allows for optimum strength without excessive casting weight  
Comparable to Victaulic's #77 and Grinnell's #7001

### Construction:

Rust inhibiting paint

### Safety notes:

WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

\* Referential image

\*\* Some features may vary without prior notice. Sale subject to inventory availability

**TECHNICAL SPECIFICATIONS**

<b>Factory Part Number</b>	C16BU
<b>Material</b>	Ductile Iron
<b>Max. End Load Lbs.</b>	34472
<b>Maximum Operating Pressure</b>	1000 PSI at 70°F (21°C)
<b>Nominal Size</b>	6"
<b>Pipe OD</b>	6.625"
<b>Seal</b>	Buna-N
<b>Weight Lb</b>	12.1600