

WILKERSON FRL'S C18 COMPACT COMBINATION UNIT



* Referential image

** Some features may vary without prior notice. Sale subject to inventory availability

DATE
: 07/09/2026 12:54 AM

SKU
: 26149

BRAND
: DIXON VALVE

MODEL
: C18-03M

Features:

Manual Drain

Transparent Bowl and Guard

F18 series Filter has a 5 micron element and a 4 oz. bowl

R18 series Regulator is self-relieving, with a 0-125 PSI adjusting range and is supplied with a GC230 gauge

L18 series Lubricator has a 4.09 oz. bowl, and adjustable oil feed and a full view sight dome

Includes (2) end blocks and (2) mounting brackets with joiner set and port O-ring

Safety notes:

FRL's are designed for air service only, unless otherwise indicated.

SCFM ratings at 150 PSIG inlet pressure

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Description	Manual Drain, Transparent Bowl and Guard
Factory Part Number	C18-03M
Flow	160 SCFM
Mandatory Pkg/Box Qty	1
Maximum Operating Pressure	150 PSIG (10.3 Bar)
Port	3/8"
Temperature Range	32°F to 125°F (0°C to 52°C)
Weight Lb	6.7600

TECHNICAL SPECIFICATIONS