

## GROOVED STANDARD COUPLING- SERIES S, STYLE 11



\* Referential image

\*\* Some features may vary without prior notice. Sale subject to inventory availability

DATE

: 04/22/2026 04:28 PM

SKU

: 23379

BRAND

: DIXON VALVE

MODEL

: C20BU

Applications:

Designed for a wide range of applications including commercial/industrial construction, mining, and process piping.

Specifications:

Underwriters Listed

Factory Mutual approved

Bolts: 2

Bolt Size: 7/8"

Bolt Length: 5"

Features:

Housing design allows for optimum strength without excessive casting weight

Comparable to Victaulic's #77 and Grinnell's #7001

Construction:

Rust inhibiting paint

Safety notes:

WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

**TECHNICAL SPECIFICATIONS**

|                                   |                        |
|-----------------------------------|------------------------|
| <b>Factory Part Number</b>        | C20BU                  |
| <b>Material</b>                   | Ductile Iron           |
| <b>Max. End Load Lbs.</b>         | 72610                  |
| <b>Maximum Operating Pressure</b> | 800 PSI at 70°F (21°C) |
| <b>Nominal Size</b>               | 10"                    |
| <b>Pipe OD</b>                    | 10.75"                 |
| <b>Seal</b>                       | Buna-N                 |
| <b>Weight Lb</b>                  | 23.9500                |