

**WILKERSON FRL'S C26
STANDARD COMBINATION UNIT**

DATE
: 04/23/2026 11:10 AM

SKU
: 26157

BRAND
: DIXON VALVE

MODEL
: C26-03M



Features:

Manual Drain

Transparent Bowl and Guard

F26 Series Filter has a 5 micron element and a 10 oz. bowl

F26 series Regulator is self-relieving with a 0-125 PSI adjusting range and is supplied with a GC230 gauge

L26 series Lubricator has a 10 oz. bowl, an adjustable oil feed and a full view sight dome

(2) modular sleeves, (2) mounting brackets (sleeve and bracket) and (2) end blocks are included

Safety notes:

FRL's are designed for air service only, unless otherwise indicated.

SCFM ratings at 150 PSIG inlet pressure

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Description	Manual Drain, Transparent Bowl and Guard
Factory Part Number	C26-03M
Flow	60 SCFM
Mandatory Pkg/Box Qty	1
Maximum Operating Pressure	150 PSIG (10.3 Bar)
Port	3/8"
Temperature Range	32°F to 125°F (0°C to 52°C)
Weight Lb	8.7880

* Referential image

** Some features may vary without prior notice. Sale subject to inventory availability

TECHNICAL SPECIFICATIONS