

**WILKERSON FRL'S C26  
STANDARD COMBINATION UNIT**

DATE  
: 07/09/2026 01:56 AM

SKU  
: 26157

BRAND  
: DIXON VALVE

MODEL  
: C26-03M



Features:

Manual Drain

Transparent Bowl and Guard

F26 Series Filter has a 5 micron element and a 10 oz. bowl

F26 series Regulator is self-relieving with a 0-125 PSI adjusting range and is supplied with a GC230 gauge

L26 series Lubricator has a 10 oz. bowl, an adjustable oil feed and a full view sight dome

(2) modular sleeves, (2) mounting brackets (sleeve and bracket) and (2) end blocks are included

Safety notes:

FRL's are designed for air service only, unless otherwise indicated.

SCFM ratings at 150 PSIG inlet pressure

WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

**TECHNICAL SPECIFICATIONS**

<b>Description</b>	Manual Drain, Transparent Bowl and Guard
<b>Factory Part Number</b>	C26-03M
<b>Flow</b>	60 SCFM
<b>Mandatory Pkg/Box Qty</b>	1
<b>Maximum Operating Pressure</b>	150 PSIG (10.3 Bar)
<b>Port</b>	3/8"
<b>Temperature Range</b>	32°F to 125°F (0°C to 52°C)
<b>Weight Lb</b>	8.7880

\* Referential image

\*\* Some features may vary without prior notice. Sale subject to inventory availability

**TECHNICAL SPECIFICATIONS**