

**WILKERSON FRL'S C28
STANDARD COMBINATION UNIT**



* Referential image

** Some features may vary without prior notice. Sale subject to inventory availability

DATE

: 04/23/2026 12:32 PM

SKU

: 26170

BRAND

: DIXON VALVE

MODEL

: C28-04MMB

Features:

Manual Drain

Metal Bowl

Quick disconnect bowl / bowl guard

Modern design and appearance

F28 series Filter has a 5 micron element and a 6 oz. bowl

R28 series Regulator is self-relieving with a 0-125 PSI adjusting range and is supplied with a GC230 gauge

L26 series Lubricator has a 6.11 oz. bowl, an adjustable oil feed and a full view sight dome

(2) end blocks and (2) mounting brackets with joiner set and port O-ring are included

Safety notes:

FRL's are designed for air service only, unless otherwise indicated.

SCFM ratings at 150 PSIG inlet pressure

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Description	Manual Drain, Metal Bowl
Factory Part Number	C28-04MMB
Flow	90 SCFM
Mandatory Pkg/Box Qty	1
Maximum Operating Pressure	250 PSIG (17.2 Bar)
Port	1/2"
Temperature Range	32°F to 150°F (0°C to 65.5°C)
Weight Lb	6.7400

- Page 1/2 -

TECHNICAL SPECIFICATIONS