

**WILKERSON FRL'S C28
STANDARD COMBINATION UNIT**



* Referential image

** Some features may vary without prior notice. Sale subject to inventory availability

DATE

: 04/23/2026 12:25 PM

SKU

: 26171

BRAND

: DIXON VALVE

MODEL

: C28-06A

Features:

Automatic Drain

Transparent Bowl and Guard

Quick disconnect bowl / bowl guard

Modern design and appearance

F28 series Filter has a 5 micron element and a 6 oz. bowl

R28 series Regulator is self-relieving with a 0-125 PSI adjusting range and is supplied with a GC230 gauge

L26 series Lubricator has a 6.11 oz. bowl, an adjustable oil feed and a full view sight dome

(2) end blocks and (2) mounting brackets with joiner set and port O-ring are included

Safety notes:

FRL's are designed for air service only, unless otherwise indicated.

SCFM ratings at 150 PSIG inlet pressure

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Description	Automatic Drain, Transparent Bowl and Guard
Factory Part Number	C28-06A
Flow	110 SCFM
Mandatory Pkg/Box Qty	1
Maximum Operating Pressure	150 PSIG (10.3 Bar)
Port	3/4"
Temperature Range	32°F to 150°F (0°C to 65.5°C)

TECHNICAL SPECIFICATIONS

Weight Lb

6.4100