

**WILKERSON FRL'S C28
STANDARD COMBINATION UNIT**



* Referential image

** Some features may vary without prior notice. Sale subject to inventory availability

DATE
: 04/23/2026 12:33 PM

SKU
: 26173

BRAND
: DIXON VALVE

MODEL
: C28-06M

Features:

- Manual Drain
- Transparent Bowl and Guard
- Quick disconnect bowl / bowl guard
- Modern design and appearance
- F28 series Filter has a 5 micron element and a 6 oz. bowl
- R28 series Regulator is self-relieving with a 0-125 PSI adjusting range and is supplied with a GC230 gauge
- L26 series Lubricator has a 6.11 oz. bowl, an adjustable oil feed and a full view sight dome
- (2) end blocks and (2) mounting brackets with joiner set and port O-ring are included

Safety notes:

- FRL's are designed for air service only, unless otherwise indicated.
- SCFM ratings at 150 PSIG inlet pressure
- WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Description	Manual Drain, Transparent Bowl and Guard
Factory Part Number	C28-06M
Flow	110 SCFM
Mandatory Pkg/Box Qty	1
Maximum Operating Pressure	150 PSIG (10.3 Bar)
Port	3/4"
Temperature Range	32°F to 150°F (0°C to 65.5°C)

TECHNICAL SPECIFICATIONS

Weight Lb

6.4100