

HYDRAULIC 4-BOLT FLANGE PIPE SOCKET WELD



* Referential image

** Some features may vary without prior notice. Sale subject to inventory availability

DATE

: 05/25/2026 06:04 PM

SKU

: 9879

BRAND

: DIXON VALVE

MODEL

: C614K1616PSW

Applications:

Flange adapters for hydraulic systems make installation of components easier, especially in applications with limited space.

Specifications:

SAE J518-1 / ISO 6162-1

Features:

Standard pressure

Flanges are constructed with an O-ring seal to eliminate leakage

Includes bolt kit with Buna O-ring

Construction:

Pad size: 1"

Available Options:

Also available in 316L stainless steel, contact Dixon

Note:

Connection type opposite 4-bolt flange connection can de-rate maximum working pressure

Safety notes:

Pressure rating given at ambient temperature 70°F

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

| | |
|-----------------------------------|-----------------------|
| Factory Part Number | C614K1616PSW |
| Fitting Type | O-ring |
| Material | Carbon Steel |
| Maximum Operating Pressure | 4600 PSI (32 MPa) |
| Port | 1" |
| Style | Code 61 |
| Torque | Grade 8 UNC: 44 lb-ft |
| Weight Lb | 1.2500 |