

HYDRAULIC 4-BOLT FLANGE PIPE SOCKET WELD

DATE
: 05/25/2026 06:04 PM

SKU
: 9884

BRAND
: DIXON VALVE

MODEL
: C614K4848PSW



Applications:

Flange adapters for hydraulic systems make installation of components easier, especially in applications with limited space.

Specifications:

SAE J518-1 / ISO 6162-1

Features:

Standard pressure

Flanges are constructed with an O-ring seal to eliminate leakage

Includes bolt kit with Buna O-ring

Construction:

Pad size: 3"

Available Options:

Also available in 316L stainless steel, contact Dixon

Note:

Connection type opposite 4-bolt flange connection can de-rate maximum working pressure

Safety notes:

Pressure rating given at ambient temperature 70°F

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

* Referential image

** Some features may vary without prior notice. Sale subject to inventory availability

TECHNICAL SPECIFICATIONS

Factory Part Number	C614K4848PSW
Fitting Type	O-ring
Material	Carbon Steel
Maximum Operating Pressure	2300 PSI (16 MPa)
Port	3"
Style	Code 61
Torque	Grade 8 UNC: 218 lb-ft
Weight Lb	8.2100