

## HYDRAULIC 4-BOLT FLANGE NPTF PORT



\* Referential image

\*\* Some features may vary without prior notice. Sale subject to inventory availability

DATE  
: 05/25/2026 06:05 PM

SKU  
: 9931

BRAND  
: DIXON VALVE

MODEL  
: C62452424NPT

#### Applications:

Flange adapters for hydraulic systems make installation of components easier, especially in applications with limited space.

#### Specifications:

SAE J518-2 / ISO 6162-2

#### Features:

High pressure

Flanges are constructed with an O-ring seal to eliminate leakage

Flat face flange must be used with O-ring flange

No bolt kit is included with flat face flange

#### Construction:

Pad size: 1-1/2"

#### Available Options:

Also available in 316L stainless steel, contact Dixon

#### Note:

Connection type opposite 4-bolt flange connection can de-rate maximum working pressure

#### Safety notes:

Pressure rating given at ambient temperature 70°F

WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

**TECHNICAL SPECIFICATIONS**

<b>Factory Part Number</b>	C62452424NPT
<b>Fitting Type</b>	Flat Face
<b>Material</b>	Carbon Steel
<b>Maximum Operating Pressure</b>	6000 PSI (40 MPa)
<b>Port</b>	1-1/2"
<b>Style</b>	Code 62
<b>Thread Size</b>	1-1/2" - 11-1/2
<b>Torque</b>	Grade 8 UNC: 218 lb-ft
<b>Weight Lb</b>	4.2000