

HYDRAULIC 4-BOLT FLANGE SAE PORT

DATE
: 05/25/2026 07:46 PM

SKU
: 9943

BRAND
: DIXON VALVE

MODEL
: C6248K3232SAE

Applications:
Flange adapters for hydraulic systems make installation of components easier, especially in applications with limited space.

Specifications:
SAE J518-2 / ISO 6162-2

Features:
High pressure
Flanges are constructed with an O-ring seal to eliminate leakage
Flat face flange must be used with O-ring flange
No bolt kit is included with flat face flange

Construction:
Pad size: 2"

Available Options:
Also available in 316L stainless steel, contact Dixon

Note:
Connection type opposite 4-bolt flange connection can de-rate maximum working pressure

Safety notes:
Pressure rating given at ambient temperature 70°F
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov



* Referential image

** Some features may vary without prior notice. Sale subject to inventory availability

TECHNICAL SPECIFICATIONS

Factory Part Number	C6248K3232SAE
Fitting Type	O-ring
Material	Carbon Steel
Maximum Operating Pressure	6000 PSI (40 MPa)
Port	2"
Style	Code 62
Thread Size	2-1/2"-12
Torque	Grade 8 UNC: 332 lb-ft
Weight Lb	7.2350