

## WILKERSON FRL'S CB6 COMPACT FILTER/REGULATOR



\* Referential image

\*\* Some features may vary without prior notice. Sale subject to inventory availability

DATE

: 07/09/2026 02:56 AM

SKU

: 26186

BRAND

: DIXON VALVE

MODEL

: CB6-02MG

Applications:

Over-under units are space savers and provide for installation in tight areas. One common inlet/outlet for both filter and regulator saves on piping costs.

Use:

Two 1/4" gauge ports located on the front and rear faces of the body. These ports may be used as additional regulated ports or for pressure gauges. Plug unused port(s).

Features:

Manual Drain

Transparent Bowl and Guard

0-125 PSIG adjusting range

5 micron reusable element

5 oz. bowl

Self-relieving standard

Diaphragm operated

Quick-disconnect bowl guard with integral plastic bowl and safety latch standard

Supplied with a GC230 gauge

Safety notes:

FRL's are designed for air service only, unless otherwise indicated.

SCFM ratings at 100 PSIG inlet pressure

WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

**TECHNICAL SPECIFICATIONS**

<b>Description</b>	Manual Drain, Transparent Bowl and Guard
<b>Factory Part Number</b>	CB6-02MG
<b>Flow</b>	64.0 SCFM
<b>Mandatory Pkg/Box Qty</b>	1
<b>Maximum Operating Pressure</b>	150 PSIG (10.3 Bar)
<b>Port</b>	1/4"
<b>Temperature Range</b>	32°F to 125°F (0°C to 52°C)
<b>Weight Lb</b>	2.5200